

Rec'd PCT/PTC 0.6 JUL 2004  
PCT/IB-02/05729

29.01.03



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets

REC'D 25 FEB 2003

WIPO

PCT

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-  
gen stimmen mit der  
ursprünglich eingereichten  
Fassung der auf dem näch-  
sten Blatt bezeichneten  
europäischen Patentanmel-  
dung überein.

The attached documents  
are exact copies of the  
European patent application  
described on the following  
page, as originally filed.

Les documents fixés à  
cette attestation sont  
conformes à la version  
initialement déposée de  
la demande de brevet  
européen spécifiée à la  
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

02075075.8

**PRIORITY DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH  
RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

R C van Dijk

DEN HAAG, DEN  
THE HAGUE, 18/12/02  
LA HAYE, LE



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets

**Blatt 2 der Bescheinigung**  
**Sheet 2 of the certificate**  
**Page 2 de l'attestation**

Anmeldung Nr.:  
Application no.:  
Demande n°: 02075075.8

Anmeldetag:  
Date of filing: 11/01/02  
Date de dépôt:

Anmelder:  
Applicant(s):  
Demandeur(s):  
Koninklijke Philips Electronics N.V.  
5621 BA Eindhoven  
NETHERLANDS

Bezeichnung der Erfindung:  
Title of the invention:  
Titre de l'invention:  
Transmission system

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:  
State:  
Pays:

Tag:  
Date:  
Date:

Aktenzeichen:  
File no.  
Numéro de dépôt:

Internationale Patentklassifikation:  
International Patent classification:  
Classification internationale des brevets:

/

Am Anmeldetag benannte Vertragsstaaten:  
Contracting states designated at date of filing:  
Etats contractants désignés lors du dépôt:

AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE/TR

Bemerkungen:  
Remarks:  
Remarques:

# Transmission system

The invention relates to a transmission system comprising a transmitter and at least one receiver, the transmitter being arranged for transmitting a plurality of signals, e.g. radio and/or television signals, the plurality of signals comprising mutually corresponding signals, e.g. analog and digital signals or standard definition (SD) and high definition (HD) signals of the same channel/programme, the receiver being arranged for receiving at least part of said plurality of signals.

The simultaneous transmission of mutually corresponding signals as defined above is sometimes referred to as simulcast. The mutually corresponding signals may be versions of the same channel/programme according to two or more standards, e.g. PAL and DVB, which are transmitted simultaneously during a transition period between these standards. Alternatively, the mutually corresponding signals may be standard definition and high definition signals of the same channel/programme.

Not every receiver may be able to receive or process, e.g. reproduce, all of the mutually corresponding signals. For instance, a standard definition television receiver in general can not receive and display high definition television programmes. Modern receivers are arranged to prepare a list of available channels/programmes for presentation to a user so that the user can select a desired channel/programme. A problem with such a list is that it contains entries for all the mutually corresponding signals, which may include signals which cannot be received or processed by the receiver. The user thus finds channels/programmes in the list which cannot be received or processed by the receiver.

It is an object of the present invention to provide a transmission system according to the preamble which does not suffer from the above mentioned problem. This object is achieved in the transmission system according to the invention, said transmission system being characterized in that the transmitter is arranged for transmitting information identifying said mutually corresponding signals and in that the receiver is arranged for receiving said information, the receiver comprising a selector for selecting on basis of said information at least one of the mutually corresponding signals. In this way the receiver can select automatically which of the mutually corresponding signals is best suited for inclusion in the list so that the user is only confronted with a single entry for each channel/programme.

The selection may also be based on the capabilities of the receiver or on the quality of the received signals. For instance, a high definition television signal may be transmitted with less power than the therewith corresponding standard definition television signal. In case of bad reception conditions the selector in a high definition television receiver  
5 may select the standard definition television signal.

By means of example the simulcast of mutually corresponding SD and HD video services and the information identifying these services will now be described in a DVB compliant system setting. DVB is a digital TV standard which is partly defined in the following document: ETSI EN 300468 "Digital Video Broadcasting (DVB) Specification for  
10 Service Information in DVB systems".

Two options are identified to create a simulcast situation for SD and HD video services:

- The SD and HD services are in fact one DVB service and the two video components are carried as two alternative video components of a single service in a single  
15 transport stream. This is called the "Single Service Configuration Option".

- The SD and HD services are two separate DVB services potentially carried in two different transport streams (be it on different frequencies and/or with a different geographical coverage e.g. using hierarchical modulation or just for bandwidth management reasons). This is called the "Multi Service Configuration Option".

#### **Single Service Configuration Option:**

This option requires that both SD and HD MPEG video elementary streams are part of a single service. In order to signal information identifying the mutually corresponding SD and HD video streams the components can be tagged with a  
25 component\_descriptor in the EIT (Event Information Table) of the event that will describe the type of video component (SD or HD) (see table 12 of the above mentioned document). The corresponding video components can be tagged with a stream\_identifier\_descriptor in the PMT (Program Map Table) for that service (tag values matching the corresponding tag fields in the EIT).

30 Automatic selection of the appropriate video service can be handled by the receiver based on the EIT signaling, the type (SD and/or HD) stream available and the decoding capabilities of the receiver.

### **Multi Service Configuration Option:**

Two signaling options are defined here to identify a service as being HD-only:

- A new service type (carried in the service\_descriptor in the SDT (Service Description Table) and optionally in the service\_list\_descriptor in the NIT (Network Information Table).
- Linkage descriptor carried in the SDT. This alternative, provides more compatibility to "existing" HD receivers but is less backward compatible to SD receivers.

The Multi Service Configuration Option requires that two services (on the same network) with essentially the same content (in SD and HD format respectively) are available (probably on different multiplexes, but with identical network\_ids). The equivalence of both services is signaled by using the same logical channel number (LCN, carried in the logical\_channel\_descriptor of the NIT for both services). Note: in order for the receiver to recognize the equivalence of the services it is essential that both are carried by the same network (i.e. are associated with the same network\_id), but it is not essential that both are carried on the same transport stream. Services with the same LCN, different service\_ids and different network\_ids are considered to be regional variants.

#### **Signalling option 1: new service type:**

The difference between the SD and the HD version of the service is indicated by the "service\_type" field in the "service\_descriptor" carried in the SDT (and if available, in the service\_list\_descriptor carried the NIT). For the SD version of the service, service type 0x01 (digital television) is used. For the HD version of the service, service type 0x81 can be used (user defined by DVB, meaning "digital HD video service with an equivalent SD service"). This definition allows SD receivers to ignore HD-only services in a fully backward compatible way, while HD receivers can easily disregard SD versions of the same service. It does require HD receivers to be aware of the new service\_type however.

#### **Signalling option 2: new linkage descriptor:**

A new type of linkage\_descriptor is introduced in the SDT: "SD service replacement link". The type\_id used could be 0x90 (DVB user defined: meaning "SD replacement service link") or a regular DVB code (e.g. 0x12) could be applied for. It should be carried in the SDT for an HD service, pointing to the equivalent SD service. SD-only

receivers can ignore services with this link and use the SD equivalent service pointed to by the link instead.

- Following text applies to signaling option 1 and signaling option 2: HD receivers may store both versions of the service as options in their service list and select the
- 5 SD service in case the reception quality of the HD service is poor. SD receivers can safely ignore HD-only services completely.
- 
-

**CLAIM:**

- Transmission system comprising a transmitter and at least one receiver, the transmitter being arranged for transmitting a plurality of signals, e.g. radio and/or television signals, the plurality of signals comprising mutually corresponding signals, e.g. analog and digital signals or standard definition and high definition signals of the same
- 5 channel/programme, the receiver being arranged for receiving at least part of said plurality of signals, characterized in that the transmitter is arranged for transmitting information identifying said mutually corresponding signals and in that the receiver is arranged for receiving said information, the receiver comprising a selector for selecting on basis of said information at least one of the mutually corresponding signals.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**